Declaration of conformity

regarding the determination of energetic efficiency according to EN 13141-7:2011-01

Flair 225 4/0 L EU ducted ventilation unit Tested unit

Brink Climate Systems B.V.

Client

KF.80.05.326.AD.01
Document number

Europäisches Testzentrum für Wohnungslüftungsgeräte (TZWL) e.V. Test laboratory

Heat recovery Efficiency

Keywords

Dortmund, 2020-08-24

Date and place of issue

Signature

P. WernsmannHead of test laboratory





	TZWL e. V. Ernst-Mehlich 44141 Dortmu		
\square	info@tzwl.de		
▣	+49 (0)231 53477-0		
₽	+49 (0)231 53	477-109	
	www.tzwl.de		
Ŵ	co-chairman [co-chairman F	rd DrIng. M. Gringel DiplIng. (FH) T. Özbiyik Prof. DrIng. U. Hahn S DiplBew. (FH) J. Köntopp	
•	tax ID 3	gistered at	
i	this document document for requires writte	ion of single parts of and the usage of this advertising purposes n evidence of TZWL e. V. s solely refer to the	

denoted serial number



Declaration of confirmity regarding the determination of energetic efficiency according to EN 13141-7:2011-01

On behalf of Brink Climate Systems B.V. the determination of energetic efficiency was conducted by Europäisches Testzentrum für Wohnungslüftungsgeräte (TZWL) e. V. in Dortmund, Germany.

Tests were carried out according to:

 EN 13141-7:2010; Ventilation for buildings - Performance testing of components/products for residential ventilation - Part 7: Performance testing of a mechanical supply and exhaust ventilation units (including heat recovery) for mechanical ventilation systems intended for single family dwellings

Technical data of the tested unit:

Manufacturer:	Brink Climate Systems B.V.	
Туре:	Flair 225 4/0 L EU	
Serial Number:	428000203202	
Year of construction:	2020	
Power supply:	230 V ~ 50 Hz	
CE-Label:	Yes	
Maximum volume flow:	225 m³/h	

Results, energetic efficiency 7°C:

Air flow	Temperature ratio, supply air $\eta_{ heta, ext{su}}$	Total electric power consumption P _E	Specific electric power consumption
[m³/h]	[%]	[W]	[W/m³/h]
40	96,9	11,6	0,29
156	92,3	27,0	0,17
225	89,2	59,5	0,26

Results, energetic efficiency 2°C:

Air flow	Temperature ratio, supply air $\eta_{ heta, su}$	Total electric power consumption P _E	Specific electric power consumption
[m³/h]	[%]	[VV]	[W/m³/h]
40	98,3	11,6	0,29
155	93,3	29,7	0,19
223	92,2	63,5	0,28

Results of performance tests of aerodynamic characteristics, of heat recovery characteristics and of the effective power consumption are taken from tests with number M.80.05.326.AD.